



International Construction Equipment  
 301 Warehouse Drive  
 Matthews, NC 28104  
 Phone: 704 821-8200  
 Email [info@iceusa.com](mailto:info@iceusa.com)

75AT		
Crowd Force	80,000 lb	36287 kg
Extraction Force	80,000 lb	36287 kg
Optional Shaft ID	7.38 in	187 mm
Optional Swivel ID	3 in	75 mm
Optional Swivel ID	4 in	100 mm
Weight with 100' Hose Bundle	4,545 lb	2062 kg
Height	60 in	1524 mm
Width w/ Leads	26 in	660 mm
Depth		
Center to Front	17 in	432 mm
Center to Rear	20 in	508 mm
Power Unit Choices *	450E, 595E or larger	
Power Min - Max *	450 - 740 HP	328 - 550 kW
High-Torque Mode		
Torque *	75000 - 88000 ft-lb	100000 - 119000 Nm
Speed *	30 rpm - 57 rpm	
Low-Torque Mode		
Torque *	33000 - 39000 ft-lb	44600 - 53000 Nm
Speed *	70 - 100 rpm	

"Due to improvements to ICE manufactured products and the EPA mandated Tier III emission regulations, unit specifications are subject to change without notice. Please contact ICE engineering department to confirm possible changes."